

Higher efficiency



Left-right twin LED job light

with preglow and afterglow functions enhances the visibility by reducing the shade of a bit.



One-touch bit installation

Quick mode-switching button

Variable speed control by trigger



Accessory

Tool catcher set
Part No. 197043-2



enables to hook the machine quickly on a snap hook of waist belt.



Makita Singapore Pte Ltd
7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE

PRINTED IN SINGAPORE



Cordless Impact Driver
DTD171

Satisfy Professional's Needs



4 assist mode
+
4 impact force
to improve
work
efficiency



Max tightening torque

180N·m



A-mode
(Assist mode)



The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.


Cordless Impact Driver DTD171	
Variable Speed	Capacity Machine Screw : M4 - M8 (5/32" - 5/16") Standard Bolt : M5 - M16 (3/16" - 5/8") High Tensile Bolt : M5 - M14 (3/16" - 9/16") Coarse thread (in length) : 22 - 125 mm (7/8" - 4-7/8")
Brake	Hex Shank 6.35 mm (1/4")
Reversing	No Load Speed (RPM) Max / Hard / Med / Soft / Wood / Bolt / T (1) / T (2) mode : 0 - 3,600 / 3,200 / 2,100 / 1,100 / 1,800 / 3,600 / 2,900 / 3,600
Built-in Job Light	Impacts Per Minute (IPM) Max / Hard / Med / Soft / Wood / Bolt / T (2) mode : 0 - 3,800 / 3,600 / 2,600 / 1,100 / 3,800 / 3,800 / 2,600
Carrying Case	Max Fastening Torque 180 N·m (1,590 in.lbs.)
	Fastening Torque Hard / Med / Soft : 170 / 50 / 20 N·m (1,510 / 440 / 180 in.lbs.)
	Vibration Level Impact tightening of fasteners of the maximum capacity of the tool : 13.5 m/s ²
	Sound Pressure Level 97 dB(A)
	Sound Power Level 108 dB(A)
	Dimensions (L x W x H) w/ BL1815N / BL1820B : 116x79x218 mm (4-9/16"x3-1/8"x8-5/8") w/ BL1830B / BL1840B / BL1850B / BL1860B : 116x79x236 mm (4-9/16"x3-1/8"x9-1/4")
	Net weight 1.2 - 1.6 kg (2.7 - 3.4 lbs.)
	Standard Equipment : Phillips Bit, Belt Clip, Battery, Charger

Enhanced Anvil holder rigidity


Material change from Needle bearing to Ball bearing provides reduction of bit wobbling.

8 + Tightening modes and Memory function for various applications

(No load speed / Maximum blows (min⁻¹))

**Wood**

Tightening long screws.
(0 - 1,800 / 3,800)



The tool drives a screw with low-speed rotation at first. After starting to impact, the rotation speed increases and reaches max speed.

**Bolt**

Loosening bolts.
(0 - 3,600 / 3,800)



This mode helps to prevent a bolt from falling off.

T1

Teks screw thin metal
Driving self-drilling screws to a thin metal like a metal stud



The tool stops rotating soon after impact starts.

T2

Teks screw thick metal
Driving self-drilling screws to a thick metal plate with good finish.




This mode helps to prevent the screws from breakage and stripping.


4 Changing the impact force (panel button)

Changing Impact force (body button)

Max



Hard



Medium



Soft



Quick mode-switching function (body button)

Impact force change with one hand

The level of impact force changes every time you press the quick mode-switching button while holding the grip.




Memory function of impact mode is equipped.

If any two modes are registered in advance, you can switch to your desired mode by just pressing quick mode-switching button.

Example of Memory function of impact mode

If you register "hard impact mode" and "Teks thin" mode, you can switch from "hard impact mode" to "Teks thin" mode by just one click of the quick mode-switching button.



18V
LITHIUM-ION

BL
MOTOR **XPT**